

FIG. 2




FIG. 3




FIG. 4




FIG. 7

DATA SIZE (Byte)		256	512	1024	2048	4096	8192	16384
COMMUNICATION TIME (ms)	SEND MODE	21	23	26	31	29	31	31
	SEND-GET MODE	25	25	26	27	28	29	34
THRESHOLD VALUE		2048 (THRESHOLD VALUE "1")	16384 (THRESHOLD VALUE "2")		--			
COMMUNICATION MODE		SEND MODE	SEND-GET MODE		SEND MODE			

FIG. 8

DATA SIZE (Byte)		256	512	1024	2048	4096	8192	16384
COMMUNICATION TIME (ms)	SEND MODE	21	23	26	31	29	31	31
	SEND-GET MODE	25	25	26	27	28	29	34
TABLE ENTRY NUMBER		0	8	64
COMMUNICATION MODE		SEND MODE		SEND-GET MODE		SEND MODE		

FIG. 10





FIG. 14



[illegible]

FIG. 16

DATA SIZE (Byte)		256	512	1024	2048	4096	8192	...
DATA TRANSMITTING/ RECEIVING TIME (ms)	OS BUFFER MODE	21	23	26	28	29	31	...
	DRIVER MODE BUFFER MODE	25	25	26	27	28	29	...

FIG. 17

